LENOSED

LN-66MIP3H

3MP Smart IR Fixed-focal Bullet Network Full Color Camera

Camera	
Image Sensor	1/3"High-resolution CMOS Sensor
Resolution	5MP
Effective Pixels	(2880*1616)
Compression	H.264/H.265/H.265+
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	NO

LENS Type	
Lens Type	Fixed
Lens	3.6mm / F1.3

Night Vision	
Infrared LED	3PCS double Chip LED, White light, infrared can be selected
Infrared Distance	25-30M
IR Status	Under 5 Lux By Camera Sensor
IR Power On	Sensor Auto Control

Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS, IP Filter
ONVIF	Support ONVIF
P2P	YES, Support QR Code
POE	Support 48-52V

Network	
Video Delay	0.3S (Within the Lan)
Main Stream 3	5MP@30fps (60HZ),5MP@25fps (50HZ)
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad

Camera	
Day/Night	Color/ B&W (IR-CUT) Smart
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	Support
ROI	/
Defog Mode	Support
BLC	Support
HDR	/
DWDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/VMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands, Czech

Interface	
Audio	Optional Audio in(Built-in)
Alarm	/
SD Card Slot	NO
RS485	/

General	
Housing	Metal+ Plastic , IP66
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	-30℃ ~ +60℃ RH95% Max
Storage Temperature	-30℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 500mA POE 48-52V

General	
Dimension	Size: 175(W) x 68(H) x 65(D)mm
Weight	Weight: 0.2Kg

www.lenosed.com