LENOSED

# LN-66MIP6H

## 6MP Smart IR Fixed-focal Bullet Network Full Color Camera

| Camera | |
|---|---|
| **Image Sensor** | 1/2.9"High-resolution CMOS Sensor |
| **Resolution** | 6MP |
| **Effective Pixels** | 3200*1800 |
| **Compression** | H.264/H.265 |
| **TV System** | PAL/NTSC |
| **Electronic Shutter Time** | Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec |
| **S/N Ratio** | ≥52dB |
| **Scanning System** | Progressive |
| **Video Output** | Network |
| **Reset Button** | NO |

| LENS Type | |
|---|---|
| **Lens Type** | Fixed |
| **Lens** | 3.6mm / F1.3 |

| Night Vision | |
|---|---|
| **Infrared LED** | 3PCS double Chip LED, White light, infrared can be selected |
| **Infrared Distance** | 25-30M |
| **IR Status** | Under 5 Lux By Camera Sensor |
| **IR Power On** | Sensor Auto Control |

| Network | |
|---|---|
| **Ethernet** | RJ-45 (10/100Base-T) |
| **Protocol** | ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS, IP Filter |
| **ONVIF** | Support ONVIF |
| **P2P** | YES, Support QR Code |
| **POE** | Support 48-52V |

| Network | |
|---|---|
| **Video Delay** | 0.3S (Within the Lan) |
| **Main Stream 3** | 6MP@30fps (60HZ),6MP@25fps (50HZ) |
| **IE Brower** | IE8-11, Google Chrome, Firefox, Safari, Mac Safari |
| **Smart Phone** | iPhone, iPad, Android, Android Pad |

| Camera | |
|---|---|
| **Day/Night** | Color/ B&W (IR-CUT ) Smart |
| **Image Config** | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) |
| **Corridor Pattern** | Support |
| **ROI** | / |
| **Defog Mode** | Support |
| **BLC** | Support |
| **HDR** | / |
| **DWDR** | Support |
| **Motion Detection** | Support |
| **Privacy Masking** | 3 Rectangular Zone |
| **Recording Mode** | NVR/VMS/Web |
| **Language** | Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands, Czech |

| Interface | |
|---|---|
| **Audio** | Optional Audio in(Built-in) |
| **Alarm** | / |
| **SD Card Slot** | NO |
| **RS485** | / |

| General | |
|---|---|
| **Housing** | Metal+ Plastic , IP66 |
| **Anti-cut Bracket** | NO |
| **IR Cut Filter** | YES |
| **Operation Temperature** | -30℃ ~ +60℃ RH95% Max |
| **Storage Temperature** | -30℃ ~ +60℃ RH95% Max |
| **Power Source** | DC12V±10%, 500mA POE 48-52V |

| General | |
|---|---|
| **Dimension** | Size: 175(W) x 68(H) x 65(D)mm |
| **Weight** | Weight: 0.2Kg |

## www.lenosed.com